



40-760-9999 Aplexol Aqua Multi Hardener

Version: 200327

: Aplexol Aqua Multi Hardener is a high-quality aliphatic isocyanate.

Properties

: Aplexol Aqua Multi Hardener is a lightfast hardener for Aplexol Aqua Finish, HD Aqua PUR and HD Anker-top Aqua water-based paint systems.

Processing

: Aplexol Aqua Multi Hardener, mixing ratio (weight) lacquer-/Harder 10:1. Stir the hardener slowly (mechanically) with the mixer running. Allow the mixture to stand/vent for approx. 5 minutes. Processing time approx. 2 hours.

Identification

: Aplexol Aqua Multi Hardener implies an identification obligation in accordance with the German Regulation on Hazardous Substances.

Notice

: Aplexol Aqua Multi Hardener has a shelf life of up to 6 months when stored properly. Opened packages must be properly closed immediately after use and processed quickly. Avoid direct heating sources.

Vlampunt

: > 21°C

Details

: the hardener is free of formaldehyde, heavy metal and insecticides. Please observe our current safety data sheet.

Safety aspects

: see information on safety data sheet.

Hazard class (transport)

: see information on safety data sheet.

The information stated has been prepared to the best of our knowledge and ability. However, the user must test the application of this product against the circumstances and possibilities that apply to him. No liability or warranty can be derived from the text of this technical description.